

Technical Datasheet



Trade name : OMNI 200
Reviewed: 27.11.2018
Date of print : 27.11.2018

Page : 1 of 1

Description

OMNI 200 is an economical, multifunctional spray with excellent capillarity. Forms a lubricating, nonresinifying, temporary anti-corrosion film. Dissolves rust and graphite, removes resinified greases and oils. OMNI 200 lubricates everything from hinges to bike pedals, protects from rust and creep current. OMNI 200 does not contain hydrocarbon solvents (e.g. petroleum), acid, silicone or Teflon. The product has excellent penetration properties, even in very tight spaces.

Chemical characterisation

Extremely purified hydrocarbons and additives.

Classification according to Regulation (EC) No.1272/2008 [CLP]

-

Transport information

ADR : -

Water hazard class (Classification according to VwVwS)

Water hazard class : 1 (Slightly hazardous to water)

Labelling for contents according to regulation (EC) No. 648/2004

-

Safety equipment

Eye / Face protection:	suitable safety goggles acc. EN 166	In case of splash
Hand protection:	suitable gloves type EN 374	In case of possible or continuous skin contact
Respiratory protection:	Combination filtering device DIN EN 14387	In case of exceeding exposure limit values

Application

Indispensable in everyday use in production, maintenance, craft, workshops, agriculture, gardening, forestry, building industry, home and hobby. OMNI 200 can also be used in dipping baths as a dehydrogenating agent. The product can also be used for efficient pre-cleaning in case of persistent resin-, grease- and oil pollution in Bio-Circle parts washer.

Technical data

Appearance :	Liquid		
Colour :	colourless		
Odour :	characteristic		
Boiling temperature :	218 - 800 °C	Solidifying temperature :	-25 °C
Flash point :	ca 200 °C	pH-value :	n.a.
Lower explosion limit :	n.a.	Viscosity (40 °C):	22 mm ² /s
Upper explosion limit :	n.a.	Density (15 °C) :	ca. 0,853 g/cm ³
VOC (EG) :	0 Wt %	VOC (CH) :	0 Wt %

Storage

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.

Storage class (acc. TRGS 510): 10

Disposal advices

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

Waste code acc. EWC/AVV for unused product	Waste code acc. EWC/AVV for packaging
13 02 05* Waste engine, gear and lubricating oils Non-chlorinated engine, gear and lubricating oils.	15 01 02 plastic packaging

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Order information

E50018	500 ml PET bottle with trigger - TU: 20x500 ml 1 Box
E02018	20 l Jerrycan
E20018	200 l Drum
E10018	1000 l IBC