

Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28 09 2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: SONAX Tyre Fix

Article number: 04323000

UFI: GU05-T0HV-H00F-E07C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Consumer uses: Private households / general public / consumers

Professional uses

Sealant

Uses advised against There is currently no information available on this.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

#### Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

# SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

#### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

#### Signal word Danger

#### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

#### Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501 (Contd. on page 2)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

(Contd. of page 1)

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

#### PRT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

#### Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Description: Formulation consisting of pressurised gas and aqueous emulsion of synthetic polymers

Dangerous components:		
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane  Flam. Gas 1A, H220; Press. Gas (Comp.), H280	0-<1%
CAS: 1336-21-6 EINECS: 215-647-6 Reg.nr.: 01-2119488876-14-xxxx	ammonia Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=1); STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	0-<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

Remove soiled clothing

If symptoms persist consult doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache Nausea Dizziness Drowsiness Skin irritation

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing agents:

Water spray

Foam

(Contd. on page 3)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

(Contd. of page 2)

Fire-extinguishing powder

Carbon dioxide

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

Aldehyde

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### SECTION 6: Accidental release measures

# **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation For non-emergency personnel

Do not inhale gases / fumes / aerosols.

Keep away from ignition sources.

Ensure adequate ventilation

#### For emergency responders

Wear protective equipment. Keep unprotected persons away.

Do not inhale gases / fumes / aerosols.

#### 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

#### 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to section 13.

# 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

#### Information about fire - and explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Highly volatile, flammable constituents are released during processing.



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

# 7.2 Conditions for safe storage, including any incompatibilities Storage:

# Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Keep container tightly sealed.

Observe official regulations on storing packagings with pressurised containers.

(Contd. on page 4)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

(Contd. of page 3)

#### Information about storage in one common storage facility:

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs. Store away from foodstuffs.

Observe local/state/federal regulations.

#### Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:			
CAS: 75-28-5 isok	outane		
OEL (Ireland) Short-term value: 1000 ppm			
CAS: 74-98-6 pro	CAS: 74-98-6 propane		
OEL (Ireland) Asphx			
CAS: 106-97-8 bu	CAS: 106-97-8 butane		
WEL (Great Britair	n) Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)		
OEL (Ireland)	Short-term value: 1000 ppm		

#### Regulatory information

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

WEL (Great Britain): EH40/2020

DNELs	
CAS: 1336-21-6	ammonia

Dermal	DNEL	6.8 mg/kg (worker) (chronic systemic effect)
Inhalative	DNEL	47.6 mg/m³ (worker) (chronic systemic effect)

#### PNECs

# CAS: 1336-21-6 ammonia

PNEC 0.007 mg/l (water)

0.001 mg/l (water (fresh water)) 0.001 mg/l (water (sea water))

Additional information: The lists valid during the making were used as basis.

#### 8.2 Exposure controls

#### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn

#### Individual protection measures, such as personal protective equipment

# General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Remove soiled clothing and wash it before wearing again.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

#### Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Ensure good ventilation/exhaustion at the workplace.

Hand protection Protective gloves

#### Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

(Contd. on page 5)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

(Contd. of page 4)

Penetration time of glove material Value for the permeation: Level Level 6 (≥480min)

Eye/face protection Safety glasses

### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Colour: White Odour: Odourless Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range -42 °C

(Active ingredient data)

**Flammability** Extremely flammable aerosol.

Lower and upper explosion limit

Lower: 1.5 Vol % Upper: 10.8 Vol %

Not applicable, as aerosol. Flash point:

Auto-ignition temperature: Not determined. Decomposition temperature: Not determined.

pH at 20 °C 8-9

(Active ingredient data)

Viscosity:

Kinematic viscosity Not determined.

Dynamic: Not determined. Solubility

Partition coefficient n-octanol/water (log value)

Not determined. Not determined. Vapour pressure:

Density and/or relative density

Density at 20 °C: 0.9-1 g/cm<sup>3</sup>

(Active ingredient data) Relative density Not determined.

Vapour density Not determined.

9.2 Other information

Appearance:

Form: Aerosol

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Not determined.

In use, may form flammable/explosive vapour-air

Not miscible or difficult to mix.

mixture.

Change in condition

Evaporation rate Not applicable.

Information with regard to physical hazard classes

**Explosives** Void Flammable gases Void

Aerosols

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void

(Contd. on page 6)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

(Contd. of page 5)

Self-heating substances and mixtures Substances and mixtures, which emit flammable	Void
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

# SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- 10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

- 10.5 Incompatible materials: No known incompatible materials.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

#### SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture

יבור ויסאויסונ	There are no occomborogram data available on time mixture.
Aquatic tox	icity:
CAS: 75-28-	
LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)
CAS: 74-98-	6 propane
LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)

(Contd. on page 7)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

(Contd. of page 6)

CAS: 106-97-8 butane

LC50 / 96 h 27.98 mg/l (fish) EC50 / 4 d 7.71 mg/l (algae)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

#### 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

#### 12.7 Other adverse effects

#### Additional ecological information:

General notes: The product may not be released into the environment without control.

#### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

#### Recommendation

Waste must be disposed of while observing the local, official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10*	packaging containing residues of or contaminated by hazardous substances
HP3	Flammable

SECTI	ON 14:	Transport	tini	format	ion

UN1950
1950 AEROSOLS AEROSOLS AEROSOLS, flammable

#### 14.3 Transport hazard class(es)

14.1 LIN number or ID number

#### ADR/RID/ADN



Class 2 5F Gases.

IMDG, IATA



Class 2.1 Gases.

(Contd. on page 8)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

		(Contd. of page
Label	2.1	
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
14.7 Maritime transport in bulk according instruments	to IMO Not applicable.	
Transport/Additional information:		
ADR/RID/ADN Limited quantities (LQ) Transport category	1L 2	
Tunnel restriction code	D	
UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 62.50 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS

National regulations:

#### Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

#### Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1 On basis of test data

Date of previous version: 22.04.2021 Version number of previous version: 5.00

# Abbreviations and acronyms:

NOEL = No Observed Effect Level NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

IOELV = indicative occupational exposure limit values

(Contd. on page 9)



Printing date 05.03.2024 Version: 6.00 (replaces version 5.00) Revision: 28.09.2023

Trade name: SONAX Tyre Fix

(Contd. of page 8)

Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
: Aerosols – Category 3
Press. Gas (Comp.): Gases under pressure – Compressed gas
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
\* Data compared to the previous version altered.